

**NOTES:**

- REFLECTANCES ASSUMED SURFACE: 20
- TASK HEIGHT: 30' AFF
- CALCULATION POINT SPACING: 5'X5' OC

DISCLAIMER:

THESE DRAWINGS ARE FOR CONCEPTUAL PURPOSES ONLY AND ARE NOT INTENDED FOR CONSTRUCTION. VALUES REPRESENTED ARE AN APPROXIMATION GENERATED FROM MANUFACTURERS PHOTOMETRIC IN-HOUSE OR INDEPENDANT LAB TEST WITH DATA SUPPLIED BY LAMP MANUFACTURERS.

STATISTICS

DESCRIPTION	SYMBOL	Avg.	Max	Min.	Max/Min	Avg/Min
Beyond Property Line	+	0.0 fc	0.2 fc	0.0 fc	N/A	N/A
Property	+	1.1 fc	25.7 fc	0.0 fc	N/A	N/A

SCHEDULE

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Light Loss Factor	Wattage
	B	8	Evergreen Lighting	AC B 42 12 FINISH CFA XX	Acadia Bollard	0.9	12
	I	3	LLI Architectural Lighting	LLI-N3.1W 65 DSP 30K 120V LENGTH	LED Neon - Dome Profile *Advise driver details, mounting accessories and power feeds*	0.9	6
	R	19	Spectrum Lighting	SP4ES 15L 30K DRIVER AR4LES FINISH FINISH XX	Estimator Series - 4" Recessed Downlight w/ wet location trim	0.9	15
	W	11	Lithonia Lighting	WDGE2 LED P1 30K 70CRI T1S	Wedge 2 Wall Pack	0.9	11.1658